

---

## OSLO ROUND CEILING/WALL

---

**Design:**

Kurt Nørregaard

**Concept:**

The fixture emits indirect symmetrical light. The shape of the shades results in lateral light distribution, creating a comfortable mood and a soft, decorative luminance-balancing effect.

**Finish:**

White, wet painted.

**Material:**

Shade: Spun aluminium. Diffuser: Sandblasted glass. Acrylic satiné shade for LED, aluminium heatsink, Ceiling box: Spun steel. Bolts: Die-cast aluminium.

**Mounting:****Weight:**

Min: 3.4 kg Max: 3.6 kg

**Class:**

Ingress protection IP20. Electric shock protection I w. ground.

**Info notes:**

For LED replacement kit please do contact Louis Poulsen. The innovation of the LED technology is constant. The specifications mentioned are based on present technology. Please find updated info on products on our website [www.louispoulsen.com](http://www.louispoulsen.com)

**Specification notes:**

Dimming only available with 1x42W HF-D.

Terminal strip: HF-std: 1x3x2.5mm<sup>2</sup>, HF-D:  
1x5x2.5mm<sup>2</sup>. LED-D and LED-DA 1x5x2.5mm<sup>2</sup>,  
Cable access: 2 at rear, Ø 20mm. Looping:  
Approved, max. 5x1.5 mm<sup>2</sup>.

## Results (4)



CCT/WATT/ LUMEN	LIGHT SOURCE	FINISH	LIGHTING CONTROL	EFFICACY	ORDER-NO.	
-	1X26W32W42WTC-TEL HF	WHT	NONE	-	5743144723	>
-	1X42WTC-TEL GX24Q-4 HF-D	WHT	DIM 1-10V	-	5743144736	>
3000K 28.0 1936	28WLED 3000K	WHT	DIM 1-10V	69	5743168880	>
3000K 28.0 1936	28WLED 3000K	WHT	DALI	69	5743168903	>